

Omni directional 3 dBi antenna 2.4 GHz
Ceiling mounting



Omni Directional Ceiling Antenna 3 dBi

This antenna is ideally suited for indoor use connected to an access point nearby over the directly attached cable. It provides ideal coverage in corridors and adjacent rooms when mounted underneath the ceiling plates. The small size and the inconspicuous shape and color do not make it obvious that it's a WLAN antenna but rather make it appear as a smoke detector. Several ways of mounting make the installation easy and quick in any situation: gluing, screwing or hooking to the ceiling grid is applicable.

Each antenna set includes:

- Antenna with 1m coax cable and connector of your choice to fit to all major access points
- Mounting accessories: two sided adhesive tape, self tapping screws, Nylon hooks

Technical Specifications of Antenna	
Electrical	
Operating Range	2400-2500 MHz
Gain, dBi	2.8 - 3.0
Horizontal Beam Width, degree	360
Vertical Beam Width, degree	45
Impedance, Ohm	50
VSWR	1.5
Side lobe, dB	< -20
Mechanical	
Weight	82 g
Dimensions	Diameter 113 mm / 34 mm thick
Cover Material	Aesthetic UV-inhibited white plastic
Polarization	Vertical
Connector Type	Choice of RP-SMA, RP-TNC, N – male, N- female

Antenna characteristics

